

INTERACTER MODEL SPECIFICATIONS

MODEL	DC OUTPUT AMPS	DC OUTPUT VOLTS	AC INPUT AMPS	AC INPUT VOLTS	AC INPUT FREQ.	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	WEIGHT (LBS.)
PS1205	5	12	1	117*	60Hz*	6.0	6.5	5.25	7.1
PS1210	10	12	2	117*	60Hz*	6.0	6.5	5.25	9.5
PS2405	5	24	2	117*	60Hz*	6.0	6.5	5.25	12.6
PS2408	8	24	3	117*	60Hz*	6.0	6.5	5.25	15.2
LS0606	6	6	1	117*	60Hz*	6.0	6.5	5.25	5.2
LS1202	2	12	2	117*	60Hz*	6.0	6.5	5.25	5.2
LS1206	6	12	2	117*	60Hz*	6.0	6.5	5.25	5.2
LS2403	3	24	2	117*	60Hz*	6.0	6.5	5.25	5.7
LS2405	5	24	3	117*	60Hz*	6.0	6.5	5.25	9.5
LS3603	3	36	2	117*	60Hz*	6.0	6.5	5.25	9.5
ICS1230	25	12	4.5	117*	60Hz*	12.0	7.0	7.0	24.0
ICS2425	25	24	7.5	117*	60Hz*	12.0	7.0	7.0	27.6
ICS3620	20	36	9.6	117*	60Hz*	12.0	7.0	7.0	32.1
ICS4820	20	48	12	117*	60Hz*	12.0	7.0	7.0	37.0
		* International voltages available							